


Natural Wood Noble Wood Oil Classic

Flügger Natural Wood products are intended for the care and maintenance of indoor natural wood. Revitalises and protects while maintaining the structure of the wood and keeping the grain visible.

Properties

Exclusive, weatherproof oil, that produces a glossy oil treatment. Contains UV filters that protect the wood from discolouration caused by the damaging rays of the sun. Prevents the formation of mould and mould growth on the surface.

- UV filter
- Exclusive
- Glossy



Use

Teak, mahogany and other precious woods, indoors and outdoors.
For example, exterior doors and garage doors.

Substrate

Must be absorbent, clean, dry, firm and suitable for surface treatment.

Treatment

Wood stain, paint and decayed wood fibres should be totally cleaned by cleaning and sanding.
Remove dirt, grime, grease and chalking materials by cleaning with Deck Cleaner.
Algae, mould and mould growth are removed by cleaning with Façade Algae Remover.
Sand uneven surfaces to a uniform finish.

Application

Brush or roller.
Decide on your mode of application according to the desired finish.
Apply wet on wet, finish by brushing in the same direction.
Repeat the treatment until the wood is saturated, and appears uniform without the formation of a layer of varnish.
Cold/ heat can affect the viscosity of the material.
Condensation must be prevented during drying/curing.
Cold and increased humidity extends drying time, full curing and recoating interval.
Increased temperature and low atmospheric humidity reduce drying time and full curing.
Always test adhesion and result before hanging.

Expected result

Colourless and glossy surfaces that highlight the grain of the wood.
Expected durability 1 year.
The durability of the surface depends on the quality of the wood, construction, method and quality of the work and exposure.
The expected durability can therefore be shorter or longer than stated.

Environmental information

Clean off the paint from tools and wash them with brush cleaner. Bring remains of fluent paint to the local recycling centre. Minimize your paint waste by pre-estimating how much paint you need. Keep the leftover paint for future use so you can effectively reduce the environmental impact.

Storage: Cool, frost-free, and tightly closed

Protection equipment: Painting: eye protection, gloves. Sanding: respiratory protection.

Technical Data

Product Type	Wood Oil
Gloss	Gloss;90
Density (kgs/l)	0.92
Solids Weight %	57
Solids Vol. %	50
Nominal spreading rate (m ² /ltr.)	10
Min. working temp. during application and drying/curing	Min. +5°C
Humidity	Maximum atmospheric humidity 80 % RH.
Drying time at 20° C, 60 % RH (Hours)	4
Recoatable at 20° C, 60 % RH (Hours)	12
Fully cured at 20° C, 60 % RH (Days)	28
Dilution	White spirit
Cleaning of Tools etc.	Brush Cleaner

Current TDS Version

June 2020