

Interior Fix primer

Product properties

Undercoat paint that ensures optimal adhesion. Used indoors on hard, smooth surfaces before treatment with finish paint.

- **Optimal adhesion**
- **Undercoat**
- **Matt surface**



Product use

Used on ceramic tiles, hard PVC, glass, laminate, melamine, previously painted alkyds, epoxy painted and industrially lacquered surfaces in dry rooms.

Substrate

Must be clean, dry, solid and suitable for surface treatment.
Water traps or the risk of water accumulation and constant water exposure must not occur.

Treatment

Remove loose material and paint by cleaning and sanding.
Remove dirt, grime, grease and chalking materials by cleaning with Fluren 37.
Water blotches, nicotine and soot must be cleaned with Fluren 49.
Sand surface to matt finish as required.
Cracks, unevenness and holes must be filled.
Prime new or bare, cleaned wood with Stop Primer.
Apply 1 time.

Application

Brush, roller or spray.
Decide your choice of tool/utensil depending on the finish.
Apply wet on wet and finish by brushing/rolling in the same direction.
Cold/heat can affect the viscosity of the material.
Material temperature for spray painting, min. 12°C.
Condensation during drying/curing must not occur.
Cold and increased humidity extends drying time, full curing and recoat interval.
Increased temperature and low atmospheric humidity reduce drying time and full curing.
Always perform a test treatment for a check and acceptance of adhesion and result.

Expected result

Matt, covered surface.
Finish treatment with paint in desired gloss and colour.

Please note!

Full adhesion is achieved after curing.

Environmental information

Minimize your paint waste by pre-estimating how much paint you need.

Remove as much paint as possible from tools before cleaning.

Paint and cleaning fluid must not be poured down drains, but collected and disposed of as environmental waste.

Empty and dry packaging should be sorted as plastic, metal handles should be removed and sorted as metal.

Store excess paint correctly so that leftovers can be used and environmental impact is minimised.

Storage: Cool, frost-free, and tightly closed

Protection equipment: Protect skin and eyes from splashes with suitable clothing, gloves and glasses. Avoid inhalation of spray mist and grinding dust. Wear suitable protective equipment, see safety data sheet for further information.

Supplementary Info

Registered in the Nordic Ecolabelling Building Products Database for products which can be used in buildings with the Swan label.

Technical Data

| | |
|---|---------------------------------------|
| Product Type | Priming paint |
| Gloss | Matte |
| Density (kgs/l) | 1.48 |
| Solids Weight % | 61 |
| Solids Vol. % | 42 |
| Nominal spreading rate (m ² /ltr.) | 8 |
| Min. working temp. during application and drying/curing | Min. +10°C |
| Humidity | Max. humidity 80 % RH. |
| Drying time at 20° C, 60 % RH (Hours) | 2 |
| Recoatable at 20° C, 60 % RH (Hours) | 12 |
| Fully cured at 20° C, 60 % RH (Days) | 28 |
| Dilution | Water, should not normally be diluted |
| Cleaning of Tools etc. | Water |

Current TDS Version

May 2024

Replaces TDS Version

February 2023