

# Spray

## Product properties

Full colour and gloss proof spray paint, indoors.

## Product use

Used to treat previously painted surfaces, wood, metal, aluminium, glass and stone.  
Metal surfaces must be primed with Spray Primer.

## Substrate

Must be clean, dry, free of grease and suitable for surface treatment.

## Treatment

Remove loose material and paint by cleaning and sanding.  
Dirt, grime, grease and spills are removed by cleaning.  
Sand hard, smooth surfaces.  
Apply a primer that suits the surface.  
Metal surfaces must be primed with Spray Primer.  
After drying, sand the primer (grit 600).

## Application

Shake for two minutes before use.  
Test on small area to check adherence and the result.  
Spraying distance 25 - 30 cm.  
Working temperature 15 - 25°C.  
Apply in several thin layers.  
Drying time depends on air temperature, humidity and applied layer thickness.  
After use, turn the can upside down and spray for several seconds.

## Good practise

Carefully cover surfaces and areas that are not to be painted.  
Ensure good ventilation.

## Expected result

Glossy covered surface.  
Resistant to dusting and light wiping with a damp cloth.  
Spray Colour cannot be treated with acrylic varnish or nitrocellulose varnish.  
Carefully load the surface until the paint is completely hardened.

## Environmental information

Clean off the paint from tools before cleaning. Bring remains of fluent paint to the local recycling centre. Minimize your paint waste by pre-estimating how much paint you need. Keep the leftover paint for future use so you can effectively reduce the environmental impact.



**Storage:** Cool, frost-free and tightly closed

## Technical Data

---

Gloss	Gloss
Solids Weight %	12.7
Min. working temp. during application and drying/curing	Min. +15°C
Humidity	Max. humidity 80 % RH.
Drying time at 20° C, 60 % RH (Hours)	1
Fully cured at 20° C, 60 % RH (Days)	1

---

### Current TDS Version

January 2022